


PRODUCT PRESENTATION

Product Line 2025



PRODUCT SERIES













IP Camera

AVColor
AVGuard
AVPano
AVPro
AVSwift

NVR

Standard
AV ETU
AV ETC

HD Camera

AVColor

AVSwift with AOC

AVSwift

XVR

Standard

AV ETU

AV ETC

<u>Others</u>

POE Switch

CMS

EagleEyes

AVTECH+




IP CAMERA

- AVGuard
- AVPano
- **AVColor**
- **AVPro**
- **AVSwift**










The **AVGuard** camera series make your system go from a passive to an active security solution. With Al detection capabilities and built-in speaker and microphone it lets you take action as soon as an event occurs. Use our EagleEyes APP to take advantage of AVGuard's two-way audio capabilities

This series features an advanced dual lighting system, that allows it to switch between IR Mode and warm light when a suspect is detected, acting as an active deterrence tool







DEMO LINK



Key Features:

- Al Smart Detection

- Ar Smart Detection
 Smart Dual Light System
 Built-in Speaker
 Built-in Microphone
 Great F1.0 / F1.6 aperture
 Starlight Sensor
 Up to 4K resolution
 WDR

- MicroSD Card Slot

DGM5206SVSGAT

DGM8208SVGAT

DGM5907SVSGAT



DGM5506SVSGAT


5MP & 8MP IP CAMERA SERIES

DGM8508SVGAT

| IMAGE | ANTECH ANTECH | | AVTECH | ANTECH . | PLATECH |
|------------------|---|--------|-------------|-------------------------|-------------------------|
| SENSOR | 1/2.8" SONY STARLIGHT CMOS | | | | |
| MAX. RESOLUTION | 2560x1944 (5MP / 25FPS) | | 4K (8MP) | / 20FPS) | 2560x1944 (5MP / 25FPS) |
| MIN. ILUMINATION | 0.001 LUX (IR OFF) 0 LUX (IR ON) | | | | |
| WDR | | | YES (120dB) | | |
| LENS | | f2.8 m | m / F1.6 | | f2.8-12mm / F1.6 PTZ |
| MICROSD | YES (256GB) | | | | |
| AI FEATURES | HUMAN AND VEHICLE SMART DETECTIO | N | HUMAN | I AND VEHICLE SMART DET | TECTION |
| AUDIO I/O | TWO WAY AUDIO (MICROPHONE & SPEAKER BUILT-IN) | | | | |

AVTECH





Take action instantly with the EagleEyes APP and elevate your security to the next level.





<u>Home</u>

DGM8707DGAT

<u>IP CAMERAS</u>

DGM8807DGAT

<u>NVRs</u>

HD CAMERAS

DGM8076SVAT

<u>XVRs</u>

POE SWITCH

DGM5216SVAT

SOFTWARE


Pano 5MP & 8MP IP CAMERA SERIES

| IMAGE | ALLECH | A/TECH CONTROL OF THE PARTY OF | Inter Control of the | Anna Contraction of the second | |
|------------------|----------------------------------|---|---|---|--|
| SENSOR | 1/2.7" C | MOS X 2 | SONY STARLIGH | IT 1/2.8" CMOS | |
| MAX. RESOLUTION | 4K (8MP / 20FPS) | | | 5MP @ 25 FPS | |
| MIN. ILUMINATION | 0.001 LUX (IR OFF) 0 LUX (IR ON) | | | | |
| WDR | DWDR | DWDR | YES (1 | 20dB) | |
| LENS | f2.8 mm | / F1.6 X 2 | f0.98mm Wide Angle | f2.8mm/F1.6 | |
| Manaan | YES (256GB) | | | | |
| MICROSD | | YES (2 | 56GB) | | |
| AI FEATURES | | | E SMART DETECTION | | |



The **AVColor** camera models take the advantages of their starlight imaging sensor, F1.0 aperture, and complementary warm lights to deliver full color images even during night time at low light environments where traditional IR cameras are only able to capture black and white images.





Key Features:

- Al Smart Detection
- Smart Warm LED
 Built-in Microphone
 Great F1.0 Aperture
 Starlight Sensor
 Up to 4K resolution
 WDR



SMARTPHONE







AVCOLOR 5MP MODEL DGM5106SVWAT

DEMO LINK

AUDIO I/O



2MP, 5MP & 8MP IP CAMERA SERIES

1 IN (MICROPHONE BUILT-IN)

DGM2103SVWHT DGM2203SVWHT DGM5206SVWAT DGM8108SVWAT MODEL DGM5106SVWAT DGM8208SVWAT IMAGE 1/2.8" SONY STARLIGHT CMOS **SENSOR** 1920 x 1080 (2MP / 30FPS) 4K (8MP / 20FPS) 2560x1944 (5MP / 25FPS) **MAX. RESOLUTION** 0.0001 LUX (IR OFF) 0 LUX (IR ON) MIN. ILUMINATION **YES (120dB) WDR** f2.8 mm / F1.0 **LENS YES (256GB) MICROSD AI FEATURES VEHICLE SMART DETECTION HUMAN AND VEHICLE SMART DETECTION**





The **AVPro** camera series is designed to meet the demands of more advanced projects and integrate with other security devices easily, offering a high performance solution for all kind of projects

With models offering up to 4K resolution, you will be able to capture all details even in low light conditions thanks to high-end starlight sensors.

Exceptional low-light performance is coupled with Al detection, and more advanced hardware features going from MicroSD card slot to Alarm I/O






Key Features:

- Al Smart Detection
- Built-in Alarm I/O
- Built-in Audio Óut
- Built-in Microphone Starlight Sensor Up to 4K resolution

- **W**DR
- MicroSD Card Slot







AWPro





AVPRO 5-50MM LENS

CAM. WITH FIXED LENS

DGM8209SVAT

DGM8449SVAT

DGM8549SVAT

DGM8757SVAT



DGM8109SVAT

AMP IP CAMERA SERIES

| IMAGE | PILECH 8 | ENTECH . | AVTECH | ANTECH | A)TECH |
|------------------|-----------------------------------|-------------|-------------|----------------------------|---------------------------|
| SENSOR | 1/2.8" SONY STARLIGHT CMOS | | | | |
| MAX. RESOLUTION | 4K (8MP / 30FPS) 4K (8MP / 20FPS) | | | | 4K (8MP / 20FPS) |
| MIN. ILUMINATION | 0.001 LUX (IR OFF) 0 LUX (IR ON) | | | | |
| WDR | | | YES (120dB) | | |
| LENS | f2.8 mr | m / F1.6 | f2.8 ~ 12m | m / F1.6 ~ F2.2 | f5.0 ~ 50mm / F1.6 ~ F2.2 |
| MICROSD | | | YES (256GB) | | |
| AI FEATURES | HUMAN AND VEHICLE SMART DETECTION | | | | |
| ALARM I/O | 1IN /1OUT | - | 1IN | /10UT | 1IN/1OUT |
| AUDIO I/O | 1 IN (MIC.) / 1 OUT (LINE) | 1 IN (MIC.) | | 1 IN (MIC.) / 1 OUT (LINE) | |

DGM5546SVAT

DGM5757SVAT



DGM5206SVAT

DGM5106SVAT

5MP IP CAMERA SERIES

DGM5446SVAT

| IMAGE | ALLECH 3 | A/TECH . | AVTECH | ALTECH | DATECH PATECH |
|------------------|-----------------------------------|-------------|-------------|----------------------------|---------------------------|
| SENSOR | 1/2.8" SONY STARLIGHT CMOS | | | | |
| MAX. RESOLUTION | 2592x1944 (5MP / 25FPS) | | | | |
| MIN. ILUMINATION | 0.001 LUX (IR OFF) 0 LUX (IR ON) | | | | |
| WDR | | | YES (120dB) | | |
| LENS | f2.8 mr | m / F1.6 | f2.8 ~ 12mm | / F1.6 ~ F2.2 | f5.0 ~ 50mm / F1.6 ~ F2.2 |
| MICROSD | YES (256GB) | | | | |
| AI FEATURES | HUMAN AND VEHICLE SMART DETECTION | | | | |
| ALARM I/O | 1IN /1OUT | - | | 1IN /1OUT | |
| AUDIO I/O | 1 IN (MIC.) / 1 OUT (LINE) | 1 IN (MIC.) | | 1 IN (MIC.) / 1 OUT (LINE) | |







Targeted to small and midsize projects, this series covers all the basics and goes beyond by offering AI detection and an overall great value and performance relation

Because accessing advanced features such as Al Human and Vehicle detection does not need to come along a high price tag.

AVTECH's AVSwift series offer the lowest pricing in the IP camera series, while borrowing some key features from the AVPro series







Key Features:

- Al Smart Detection
 Built-in Microphone
 Starlight Sensor*
 Up to 4K resolution
 DWDR / WDR







<u>Home</u>

DGM8108SVAT

<u>IP CAMERAS</u>

DGM8208SVAT

<u>NVRs</u>

HD CAMERAS

DGM8448SVAT

<u>XVRs</u>

POE SWITCH

DGM8548SVAT

SOFTWARE

Swift 8MP IP CAMERA SERIES

| IMAGE | ANTECH OF THE CHARLES | AVTECH | | | |
|------------------|--|------------------------------|--|--|--|
| SENSOR | 1/2.8" SONY STARLIGHT CMOS | | | | |
| MAX. RESOLUTION | 3840 x 2160 (8MP / 20FPS) | | | | |
| MIN. ILUMINATION | 0.001 LUX (IR OFF) 0 LUX (IR ON) | | | | |
| WDR | YES | (120dB) | | | |
| LENS | f2.8 mm / F1.6 | f2.8 ~ 12mm / F1.6 ~ F2.2 | | | |
| IR LED | 18 UNITS (30m) | 4 UNITS (40m) 20 UNITS (30m) | | | |
| AI FEATURES | HUMAN AND VEHICLE SMART DETECTION | | | | |
| PUSH VIDEO | YES (WITH AVTECH NVR) | | | | |
| AUDIO I/O | 1 IN (MIC.) | | | | |

AUDIO I/O

Swift 5MP IP CAMERA SERIES

MODEL DGM5104SCT DGM5103AGCAT DGM5203AGCAT DGM5345GCAT DGM5545GCAT **AWTECH** AVTECH **IMAGE**







| SENSOR | 1/2.9" CMOS | 1/3" CMOS | | | | |
|------------------|---------------------------------|-----------------------|---------------------------|--|--|--|
| MAX. RESOLUTION | 2560x1944 (5MP / 25FPS) | | | | | |
| MIN. ILUMINATION | 0.01 LUX (IR OFF) 0 LUX (IR ON) | | | | | |
| WDR | DIGITAL WDR | | | | | |
| LENS | f3.6 mm / F1.6 | f2.8 mm / F1.6 | f2.8 ~ 12mm / F1.6 ~ F2.2 | | | |
| IR LED | 4 Units (30m) | 18 UNITS (30m) | 20 UNITS (30m) | | | |
| AI FEATURES | HUMAN SMART DETECTION | | | | | |
| PUSH VIDEO | | YES (WITH AVTECH NVR) | | | | |
| | | | | | | |

1 IN (MIC.)



DGM3104SCT

<u>Home</u>

DGM3103SCT

<u>IP CAMERAS</u>

DGM3203SCT

<u>NVRs</u>

DGM3436GCT

HD CAMERAS

<u>XVRs</u>

DGM3345SCHT

POE SWITCH

SOFTWARE


DGM3545SCHT

Swift 3MP IP CAMERA SERIES

| IMAGE | DITECH 2 | AJTECH | ANTECH | ANTECH | ANTECH | AFTECH |
|--------------------------|--|---------------------------------|----------|------------------------------|----------------|----------------|
| SENSOR | 1/2.8" CMOS | 1/2.7" | СМОЅ | 1/2.9" CMOS | 1/2.7" | CMOS |
| MAX. RESOLUTION | | 2304×1296 (3MP / 25FPS) | | | | |
| MIN. ILUMINATION | | 0.01 LUX (IR OFF) 0 LUX (IR ON) | | | | |
| WDR | | | DIGITA | AL WDR | | |
| LENS | f3.6 mm / F1.6 | f2.8 mr | n / F1.6 | f2.8 ~ 12mm / F1.6 ~ F2.2 | f2.8 ~ 12mm | / F1.6 ~ F2.2 |
| IR LED | 4 Units (30m) | 18 UNITS | s (30m) | 4 UNITS (40m) | 18 UNITS (30m) | 20 UNITS (30m) |
| AI FEATURES / SD CARD | HUMAN SMART DETECTION SD CARD SLOT HUMAN SMART DETECTION | | | RT DETECTION | | |
| PUSH VIDEO | | YES (WITH AVTECH NVR) | | | | |
| AUDIO I/O | 1 IN (MIC.) | | | | | |

INSWIFT IP PTZ SERIES

| MODEL | DGM2937SVAT | DGM5937SVAT | DGM8937SVAT |
|----------------------|-------------------------|----------------------------------|---|
| IMAGE | ANTECH C | B/TECH C | EXTECH C. |
| SENSOR | | 1/2.8" SONY STARLIGHT CMOS | |
| MAX. RESOLUTION | 1920x1080 (2MP / 30FPS) | 2560x1944 (5MP / 25FPS) | 3840 x 2160 (8MP / 20FPS) |
| MIN. ILUMINATION | | 0.001 LUX (IR OFF) 0 LUX (IR ON) | |
| WDR | | YES (120dB) | |
| LENS | 4.7-94mm/F | F1.6-F3.5 (20X) | 4.5-148.5mm / F1.6-F3.5 (33X) |
| IR LED | | 8 UNITS (120m) | |
| AI FEATURES | HUMAN SMART DETECTION | HUMAN AND VEHICLE SMART DETE | CTION & AI BASED AUTOTRACKING |
| PUSH VIDEO / SD CARD | YES (WITH AVTECH NVR) | YES (WITH AVTECH NVR) | YES (WITH AVTECH NVR) / SD SLOT |
| AUDIO I/O | | 1 IN (MIC.) / 1 LINE OUT | |



AVTECH

With decades of experience releasing leading recording solutions to the market, AVTECH provides a wide range of recording options for all kind

of projects

- Standard Line
- **AV-ETU Line**
- **AV-ETC Line**

FUNCTIONS

Upgrade your IP system into an Al-enabled solution with our NVRs





Detection



Detection





Detection







Counting

• Al Based Face, Human, & Vehicle Detection

- IVS functions based on AI
- Al Event Smart Search
- Support for all IP cameras (AVTECH, ONVIF & RTSP)







Device

Smart

Scenario

Standard

GUI DEMO

actions and operation of the system based on determined events set by the user achieving a device that fully adapts to the specific needs of the user thanks to its built-in rule engine

Furthermore with its advanced hardware features it offers easy integration with external systems such as alarms and audio devices



<u>Home</u>

<u>IP CAMERAS</u>

<u>NVRs</u>

HD CAMERAS

<u>XVRs</u>

POE SWITCH

<u>SOFTWARE</u>

BUILT-IN AI STANDARD H.265 4K NVR SERIES

| MODEL | DGH1103BIX | DGH1107BIX | DGH2114BIX | AVH2109AIX | AVH2117AIX |
|----------------|--------------------|-------------------------------|--|------------------------|--------------------|
| IMAGE | AFTICH © 5 | Аттен | AFTICM | AFTICA | AMICS |
| CHANNEL NUMBER | 4CH | 9CH | 16CH | 9CH | 16CH |
| AI FUNCTION | HUMAN | I / VEHICLE / FACE DETECTIO | ON / PERIMETER INTRUSION / | FLOW COUNTING / VIRTUA | L FENCE |
| VIDEO OUTPUT | | | HDMI / VGA / Composite | | |
| HDD STORAGE | |) / EXPANDABLE THROUGH ATA | SATA HDD x 2 (UP TO 40TB) / EXPANDABLE THROUGH eSATA | | |
| MAX. RECORDING | 4K (8MP) @ 120 IPS | 4K (8MP) @ 270 IPS | 4K (8MP) @ 480 IPS | 4K (8MP) @ 270 IPS | 4K (8MP) @ 480 IPS |
| PUSH VIDEO | PUSH W!DEO | PUSH W!DEO | PUSH W!DEO | PUSH W!DEO | PUSH W!DEO |
| PoE BUILT-IN | - | - | - | 8 PoE PORTS | 16 PoE PORTS |
| ALARM I/O | - | - | - | 4 IN / | 1 OUT |
| RS485 | YES | YES | YES | YES | YES |

BUILT-IN AI STANDARD H.265 4K NVR SERIES

| MODEL | AVH8516AIX | AVH8536AIX | AVH8564AX |
|----------------|-------------------------------|---------------------------------------|-------------------------------|
| IMAGE | | | |
| CHANNEL NUMBER | 16CH | 36CH | 64CH |
| AI FUNCTION | HUMAN / VEHICLE / FACE DE | ETECTION / PERIMETER INTRUSION / FLOW | COUNTING / VIRTUAL FENCE |
| VIDEO OUTPUT | | HDMI / VGA / Composite | |
| HDD STORAGE | | SATA HDD x 8 (UP TO 160TB) | |
| MAX. RECORDING | 4K (8MP) @ 480 IPS | 4K (8MP) @ 1080 IPS | 4K (8MP) @ 960 IPS |
| PUSH VIDEO | PUSH W!DEO | PUSH W!DEO | PUSH W!DEO |
| COMPRESSION | I+265 COMPRESSION | I-1265 COMPRESSION | I-1265 COMPRESSION |
| ALARM I/O | 4 IN / 1 OUT | 4 IN / 1 OUT | 4 IN / 1 OUT |
| AUDIO I/O | 1 IN (MIC IN) / 1 OUT or HDMI | 1 IN (MIC IN) / 1 OUT or HDMI | 1 IN (MIC IN) / 1 OUT or HDMI |
| RS485 | YES | YES | YES |

STANDARD H.265 4K NVR SERIES

| MODEL | DGH1103BX | DGH1108BX | DGH2115BX | AVH2109AX | AVH2117AX | |
|----------------|-------------------------------|-------------------------------|------------------------|--------------------------|--------------------|--|
| IMAGE | Artich © a | Aftech | APTECH 100mg | AFTICH | AFTICA | |
| CHANNEL NUMBER | 4CH | 9CH | 16CH | 9CH | 16CH | |
| VIDEO OUTPUT | | | HDMI / VGA / Composite | | | |
| HDD STORAGE | SATA HDD x 1 (UP TO 20TB) eSA |) / EXPANDABLE THROUGH ATA | SATA HDD x 2 (U | IP TO 40TB) / EXPANDABLE | THROUGH eSATA | |
| MAX. RECORDING | 4K (8MP) @ 120 IPS | 4K (8MP) @ 270 IPS | 4K (8MP) @ 480 IPS | 4K (8MP) @ 270 IPS | 4K (8MP) @ 480 IPS | |
| PUSH VIDEO | PUSH WIDEO | PUSH W!DEO | PUSH WIDEO | PUSH W!DEO | PUSH WIDEO | |
| PoE BUILT-IN | - | - | - | 8 PoE PORTS | 16 PoE PORTS | |
| ALARM I/O | - | - | - | - 4 IN / 1 OUT | | |
| AUDIO I/O | - | - | - 1IN/1OUT | | | |
| RS485 | YES | YES | YES | YES | YES | |

<u>Home</u>

IP CAMERAS

<u>NVRs</u>

HD CAMERAS

<u>XVRs</u>

POE SWITCH

<u>SOFTWARE</u>

STANDARD H.265 4K NVR SERIES

| MODEL | AVH8516AX | AVH8536AX | AVH8564AX |
|------------------------|---------------------------|----------------------------|---------------------------|
| IMAGE | | | |
| CHANNEL NUMBER | 16CH | 36CH | 64CH |
| VIDEO OUTPUT | | HDMI / VGA / Composite | |
| HDD STORAGE | | SATA HDD x 8 (UP TO 160TB) | |
| MAX. RECORDING | 4K (8MP) @ 480 IPS | 4K (8MP) @ 1080 IPS | 4K (8MP) @ 960 IPS |
| PUSH VIDEO | PUSH | PUSH | DUCH |
| | WIDEO | W!DEO | PUSH W!DEO |
| COMPRESSION | | | |
| COMPRESSION ALARM I/O | IH265 | IH265 | ₩!DEO |
| | VIDEO I+265 COMPRESSION | VIDEO I-1265 COMPRESSION | VIDEO I+265 COMPRESSION |





The **AV-ETU** line of recorders implements a fully redesigned interface for ease of use providing a plug & play experience for all AVTECH users. The ETU series allows you to avoid timeconsuming setup and focus on what is truly important.

This line of recorders allows you to see as many ETU devices simultaneously as needed without a CMS license. Its dedicated AVTECH desktop application lets you view all your ETU recorders from a single PC and screen becoming a suitable solution for all sizes of businesses and projects.









The AV-ETC (Easy To Customize) line of recorders implements the same easy and convenient experience as the AV-ETU line, while it offers a neutral and customizable interface, suitable for those users looking to promote their own brands.

This line of recorders also come with dedicated neutral mobile APPs and CMS for a fully independent promotion and experience.









HD CAMERAS

- AVColor
- <u>AVSwift with AOC</u>
- **■** <u>AVSwift</u>





DGC2103FW

DGC2105ATW

DGC2205ATW



DGC2003FW

| IMAGE | ANTECH OD OT OT OT OT OT OT OT OT OT | ALTECH (C) |
|------------------|--|--|
| SENSOR | 1/3" CMOS | 1/2.9" CMOS |
| MAX. RESOLUTION | 1920 x 1080 (2MP / 30FPS) | 1920 x 1080 (2MP / 30FPS) |
| MIN. ILUMINATION | 0.01 LUX (IR OFF) 0 LUX (IR ON) | 0.01 LUX (IR OFF) 0 LUX (IR ON) |
| WDR | DIGITAL WDR | DIGITAL WDR |
| LENS | f3.6 mm / F2.0 | f3.6 mm / F1.6 |
| VIDEO MODE | TRIBID 3-in-1 (TVI / CVI / AHD) | QUADBRID 4-in-1 (TVI / CVI / AHD / CVBS) |
| AUDIO I/O | | 1 IN (MICROPHONE BUILT-IN) |
| | | |

DGC5104AFW

DGC8106ATW

DGC8206ATW



DGC5204AFW

| IMAGE | AMECH (C) | ELLECH C |
|------------------|--|----------------------------------|
| SENSOR | 1/2.5" CMOS | 1/2.8" SONY STARLIGHT CMOS |
| MAX. RESOLUTION | 2560x1944 (5MP / 12.5FPS) | 4K (8MP / 20FPS) |
| MIN. ILUMINATION | 0.01 LUX (IR OFF) 0 LUX (IR ON) | 0.001 LUX (IR OFF) 0 LUX (IR ON) |
| WDR | DIGITAL WDR | YES (120dB) |
| LENS | f3.6 mm / F1.6 | f3.6 mm / F1.6 |
| VIDEO MODE | QUADBRID 4-in-1 (TVI / CVI / AHD / CVBS) | |
| AUDIO I/O | 1 IN (MICROPHONE BUILT-IN) | |
| | | |

MODEL

DGC8206AT

DGC8446F*

DGC8646F*



DGC8106AT

| IMAGE | A/TECH | AVTECH | AJTECH 6 | ANTECH CO. | |
|------------------|----------------------------------|------------------|--|--|--|
| SENSOR | 1/2.8" SONY STARLIGHT CMOS | | | | |
| MAX. RESOLUTION | 4K (8MP / 20FPS) | | | | |
| MIN. ILUMINATION | 0.001 LUX (IR OFF) 0 LUX (IR ON) | | | | |
| WDR | | YES (12 | 20dB) | | |
| LENS | f3.6 mr | m / F1.6 | f2.8 ~ 12mm / F1.4 | | |
| VIDEO MODE | QUADBRID 4-in-1 (TV | /I/CVI/AHD/CVBS) | QUADBRID 4-in-1 (TVI / CVI / AHD / CVBS) | | |
| AUDIO I/O | 1 IN (MICROPH | ONE BUILT-IN) | - | | |
| | | | | | |



WITH AOC 5MP CAMERA SERIES

| MODEL | DGC5005AT | DGC5104AF | DGC5204AF | DGC5446SE | DGC5646 |
|------------------|--|----------------|-------------------------------|---------------------|--|
| IMAGE | AVTECH | A/TECH | AVTECH | ANTECH | Prince Control of the |
| SENSOR | | | 1/2.5" CMOS | | |
| MAX. RESOLUTION | | | 5MP / 20FPS | | |
| MIN. ILUMINATION | | 0 | .01 LUX (IR OFF) 0 LUX (IR ON |) | |
| WDR | | | DIGITAL WDR | | |
| LENS | | f3.6 mm / F1.6 | | | nm / F1.4 |
| VIDEO MODE | QUADBRID 4-in-1 (TVI / CVI / AHD / CVBS) | | | QUADBRID 4-in-1 (TV | /I / CVI / AHD / CVBS) |
| AUDIO I/O | 1 IN (MICROPHONE BUILT-IN) | | | 1 IN (MICROPH | ONE BUILT-IN) |
| | | | | | |



WITH AOC 2MP CAMERA SERIES

| MODEL | DGC2005AT | DGC2105ATS | DGC2205ATS | | |
|------------------|--|------------------|------------|--|--|
| IMAGE | AVTECH | ANTECH OF ANTECH | AVITECH | | |
| SENSOR | | 1/ 2.9" CMOS | | | |
| MAX. RESOLUTION | | 1080P@25/30FPS | | | |
| MIN. ILUMINATION | 0.01 LUX (IR OFF) 0 LUX (IR ON) | | | | |
| WDR | | DIGITAL WDR | | | |
| LENS | f3.6 mm / F1.6 | | | | |
| VIDEO MODE | QUADBRID 4-in-1 (TVI / CVI / AHD / CVBS) | | | | |
| AUDIO I/O | 1 IN (MICROPHONE BUILT-IN) | | | | |
| | | | | | |




5MP CAMERA SERIES

| MODEL | DOCEMETO | DCCEQUETC | DCCE20ETCCE |
|------------------|---------------------|--|--------------------|
| MODEL | DGC5105TS | DGC5205TS | DGC5205TSSE |
| IMAGE | E G G | ATTECH . | ANTECH |
| SENSOR | | 1/2.5" CMOS | |
| MAX. RESOLUTION | | 5MP / 20FPS | |
| MIN. ILUMINATION | | 0.01 LUX (IR OFF) 0 LUX (IR ON) | |
| WDR | | DIGITAL WDR | |
| LENS | f3.6 m | m / F1.6 | f2.8 ~ 12mm / F1.4 |
| VIDEO MODE | QUADBRID 4-in-1 (TV | QUADBRID 4-in-1 (TVI / CVI / AHD / CVBS) | |
| | | | |



2MP CAMERA SERIES

| MODEL | DGC2103F | DGC2003F | DGC2101F | DGC2004F | DGC1104RXFT | DGC1306XFT | DGC1304XFTSE |
|------------------|--|------------------|--|------------------|----------------------------|---------------------|---|
| IMAGE | ANTECH PATECH | AVTECH | AVTECH ADD | A/TECH | рлесн | | рлесн Оправана на применента |
| SENSOR | 1/3" CMOS | | | 1/2.7" CMOS | 1/ 2.7" | смоѕ | |
| MAX. RESOLUTION | 1080P@25/30FPS | | 1080P@25/30FPS | | 1080P@25/30FPS | | |
| MIN. ILUMINATION | 0.01 LUX (IR OFF) 0 LUX (IR ON) 0.1 LUX (IR OFF) 0 LUX (IR ON) | | 0.01 LUX (IR OFF) 0 LUX (IR ON) 0.1 LUX (IR OFF) 0 LUX (IR ON) | | 0.01 LUX (IR OFF | | |
| WDR | DIGITAL WDR | | DIGITAL WDR | | DIGITAL WDR | | |
| LENS | f3.6 mm / F2.0 | | f3.6 mm / F1.8 | | f2.8 ~ 8.0mm / F1.6 ~ F2.8 | | |
| VIDEO MODE | TRIBRID 3-in-1 (| TVI / CVI / AHD) | QUADBRID 4-in-1 (TV | /I/CVI/AHD/CVBS) | TVI | QUADBRID 4-in-1 (TV | /I / CVI / AHD / CVBS) |



With decades of experience releasing leading recording solutions to the market, AVTECH provides a wide range of recording options for all kind

of projects



- Standard Line
- **AV-ETU Line**
- **AV-ETC Line**

FUNCTIONS

Turn your old analog system into an Al-enabled solution with our XVRs



Virtual Fence





Detection

Vehicle Detection






Perimeter Detection

Flow Counting

• Al Based Face, Human, & Vehicle Detection

- IVS functions based on AI
- Al Event Smart Search
- Support for all analog cameras (TVI, AHD, CVI, 960H).
















STANDARD SERIES

The AVPro line of recorders offers a great degree of customization when it comes to actions and operation of the system based on determined events set by the user achieving a device that fully adapts to the specific needs of the user

Furthermore with its advanced hardware features it offers easy integration with external systems such as alarms and audio devices



<u>IP CAMERAS</u>

<u>NVRs</u>

HD CAMERAS

<u>XVRs</u>

POE SWITCH

<u>SOFTWARE</u>

AI H.265 XVR DGD SERIES

| MODEL | DGD1005AIX | DGD1009AIX | DGD2017AIX | AVZ4117AIX (TBR) | AVZ4032AIX | |
|-------------------------------|--|---------------------------------|--|--|--|--|
| IMAGE | Aftical | AFTICH | Artica | APEN MINISTER | APSK MANAGER | |
| CHANNEL NUMBER | 4CH | 8CH | 16CH | 16CH | 36CH (4CH IP) | |
| AI FUNCTION | HUMAN / VEHICLE / FACE DETECTION / PERIMETER INTRUSION / FLOW COUNTING / VIRTUAL FENCE | | | | | |
| VIDEO OUTPUT | | | HDMI / VGA / Composite | | | |
| HDD STORAGE | |) / EXPANDABLE THROUGH ATA | SATA HDD x 2 (UP TO 40TB) / EXPANDABLE THROUGH eSATA | SATA HDD x 4 (UP TO 80TB) / EXPANDABLE THROUGH eSATA | SATA HDD x 4 (UP TO 80TB) / EXPANDABLE THROUGH eSATA | |
| MAX. RECORDING ANALOG / IP | 5MP @ 24 IPS / 5MP @ 60 IPS | 5MP @ 56 IPS / 5MP @ 120 IPS | 5MP @ 96 IPS / 5MP @ 180 IPS | 4K @ 120 IPS / 4K @ 192 IPS | 5MP @ 192 IPS / 5MP @ 480 IPS | |
| PUSH VIDEO | PUSH W!DEO | PUSH W!DEO | PUSH W!DEO | PUSH W!DEO | PUSH W!DEO | |
| IP CAMERA CHANNELS | 4CH | 8CH | 16CH | 16CH | 36CH | |
| ALARM I/O | 4 IN / 1 OUT | | | | | |
| AUDIO I/O,RS485 | 4 IN / 1 OUT, YES 16 IN / 2 OUT, YES | | | | | |

IP CAMERAS

<u>NVRs</u>

HD CAMERAS

<u>XVRs</u>

POE SWITCH

<u>SOFTWARE</u>

STANDARD H.265 XVR DGD SERIES

| MODEL | DGD1005AX | DGD1009AX | DGD2109AV | DGD2017AX | | |
|----------------------------|-------------------------------|------------------------------|-------------------------------|------------------------------|--|--|
| IMAGE | ATTECH 9 5 1451ms | A/TECH © ā | ATTCH | AFTECH | | |
| CHANNEL NUMBER | 4CH | 8CH | 8CH | 16CH | | |
| VIDEO OUTPUT | HDMI / VGA / Composite | | | | | |
| HDD STORAGE | SATA HDD x 1 (UP TO 20TB) / E | XPANDABLE THROUGH eSATA | SATA HDD x 2 (UP TO 40TB) / E | EXPANDABLE THROUGH eSATA | | |
| MAX. RECORDING ANALOG / IP | 5MP @ 24 IPS / 5MP @ 60 IPS | 5MP @ 56 IPS / 5MP @ 120 IPS | 4K @ 60 IPS / 4K @ 96 IPS | 5MP @ 96 IPS / 5MP @ 180 IPS | | |
| PUSH VIDEO | PUSH W!DEO | PUSH WIDEO | PUSH W!DEO | PUSH W!DEO | | |
| IP CAMERA CHANNELS | 4CH | 8CH | 8CH | 16CH | | |
| ALARM I/O | 4 IN / 1 OUT | | | | | |
| AUDIO I/O | 4 IN / 1 OUT | | | | | |
| RS485 | YES | YES | YES | YES | | |

IP CAMERAS

<u>NVRs</u>

HD CAMERAS


<u>XVRs</u>

POE SWITCH

<u>SOFTWARE</u>

STANDARD H.265 XVR AVZ SERIES

| MODEL | AVZ4017AX | AVZ4117AX | AVZ4032AX |
|----------------------------|--|--|-------------------------------|
| IMAGE | ACTION AND ADDRESS OF THE PARTY | Afficial management of the second of the sec | Afficia someone |
| CHANNEL NUMBER | 16CH 16CH | | 36CH (4CH IP) |
| VIDEO OUTPUT | | HDMI / VGA / Composite | |
| HDD STORAGE | SATA HDD x 4 (UP TO 80TB) | SATA HDD x 4 (UP TO 80TB) | SATA HDD x 4 (UP TO 80TB) |
| MAX. RECORDING ANALOG / IP | 5MP @ 96 IPS / 5MP @ 180 IPS | 4K @ 120 IPS / 4K @ 192 IPS | 5MP @ 192 IPS / 5MP @ 480 IPS |
| PUSH VIDEO | (!) PUSH W!DEO | PUSH W!DEO | PUSH W!DEO |
| IP CAMERA CHANNELS | 16CH | 16CH | 36CH |
| ALARM I/O | 4 IN / 1 OUT | 4 IN / 1 OUT | 4 IN / 1 OUT |
| AUDIO I/O | 4 (BUILT-IN) + 12 (EXTERNAL) / 1 OUT | 16 IN / 2 OUT | 16 IN / 2 OUT |
| IVS | YES | YES | YES |





The AV-ETU line of recorders implements a fully redesigned interface for ease of use providing a plug & play experience for all AVTECH users. The ETU series allows you to avoid time-consuming setup and focus on what is truly important.

The ETU line of recorders allows you to see as many ETU devices simultaneously as needed without a CMS license. Its dedicated AVTECH desktop application lets you view all your ETU recorders from a single PC and screen becoming a suitable solution for all sizes of businesses and projects.







The AV-ETC (Easy To Customize) line of recorders implements the same easy and convenient experience as the ETU line, while it offers a neutral and customizable interface, suitable for those users looking to promote their own brands.

The ETC line of recorders also come with dedicated neutral mobile APPs and CMS for a fully independent promotion and experience.









designed to power and connect devices for projects of any scale

PoE switches

versatile range of

AVTECH

- FE POE LINE
- **GE POE LINE**
- MANAGED GE POE LINE



FE POE SWITCH LINE

| MODEL | DGS4200PE | DGS8100PE | DGSF210PF | DGSF210PE | DGSO220PE |
|--------------|--|---|-------------------------------------|----------------------------------|--|
| IMAGE | FITECH No. 100 100 100 100 100 100 100 100 100 10 | EXTECH TO THE | | MTCH S= | ACTION TO THE PARTY OF THE PART |
| PORTS | 4FE+2FE(UP-LINK) | 8FE(PoE)+1FE(UP-LINK) | 16xFE & + 2xGE (UP-LINK) + 2xSFP | 15FE & 1GE+2GE(UP- LINK)+1SFP | 24FE(PoE)+2GE(UP-LINK) +2SFP |
| TRANSMISSION | 130M(100Mbps) / 250M(10Mbps) | 130M(100Mbps) / 250M(10Mbps) | 130M(100Mbps) / 250M(10Mbps) | 130M(100Mbps) / 250M(10Mbps) | 130M(100Mbps) / 250M(10Mbps) |
| POE PORTS | 4 | 8 | 16 | 16 | 24 |
| PROTECTION | 6KV Lightning protection 8KV electro-static protection Short-circuit protection Over-Temperature protection Surge Protection | | | | |
| BANDWIDTH | 1.2Gbps | 1.8Gbps | 11Gbps. | 11Gbps. | 12.8Gbps |
| MAC ADDRESS | 2 | K | | 8K | |

GE POE SWITCH LINE

| MODEL | DGS4101PGE (Outdoor Extender) | DGS4110PG | DGS8220PG | DGSF220PG | DGSO020PG | DGS8221PG (Outdoor) |
|--------------|--|--|--------------------------------|-------------------------------------|---|---|
| IMAGE | Total Area Area Area Area Area Area Area Area | EXTECH TO THE PARTY OF THE PART | Articu | | ************************************** | AFTECH CONTROL OF THE PARTY OF |
| PORTS | 4xGE + 1xGE (UP- LINK) | 4GE(POE)+1GE(UP- LINK)+1SFP | 8GE(PoE)+2GE(UP- LINK)+2SFP | 16GE(PoE)+2GE(UP- LINK) +2SFP | 24GE(PoE)+2 GE Uplink +2SFP AI Gigabit PoE Switch | 8GE(PoE)+2GE(UP- LINK)+2SFP |
| TRANSMISSION | 130M(1000Mbps) | 130M(1000Mbps) | 130M(1000Mbps) | 130M(1000Mbps) | 130M(1000Mbps) | 130M(1000Mbps) |
| POE PORTS | 4 | 4 | 8 | 16 | 24 | 8 |
| PROTECTION | 6KV Lightning protection 8KV electro-static protection Short-circuit protection Over-Temperature protection Surge Protection | | | | | +IP65 |
| BANDWIDTH | 10Gbps | 12Gbps | 24Gbps | 40Gbps | 56Gbps | 24Gbps |
| MAC ADDRESS | 8K | | | | | |



<u>IP CAMERAS</u>

<u>NVRs</u>

HD CAMERAS

<u>XVRs</u>

POE SWITCH

<u>SOFTWARE</u>

GE L2+ MANAGED POE SWITCH LINE

| MODEL | DGS8020PGM | DGSF020PGM | DGSO040PGM |
|--------------|--|--|--------------------------------------|
| IMAGE | AVTECH Form Form | A/TECH | A/TECH |
| PORTS | 8GE + 2SFP L2 Managed PoE Switch | 16GEP+2SFP, Gigabit Managed PoE Switch | 24GE + 4SFP L2 Managed PoE Switch |
| TRANSMISSION | 100М(1000Мbps) | 100М(1000Мbps) | 100M(1000Mbps) |
| POE PORTS | 8 | 16 | 24 |
| PROTECTION | | 6KV Lightning protection 8KV electro-static protection Short-circuit protection Over-Temperature protection Surge Protection | |
| BANDWIDTH | 20Gbps | 32Gbps | 56Gbps |
| MAC ADDRESS | | 8K | |

IP CAMERAS

NVRs


HD CAMERAS

<u>XVRs</u>

CMS

Our CMS lets you manage your AVTECH system from your PC. With three different versions available there is a suitable solution for systems of all sizes.







<u>IP CAMERAS</u>

<u>NVRs</u>

HD CAMERAS

<u>XVRs</u>

POE SWITCH

<u>SOFTWARE</u>

CMS

| VERSION | CMS LITE | CMS PLUS (LIVE FREE) | CMS PLUS | CMS PRO |
|--|----------|----------------------|------------|------------|
| DEVICE MANAGEMENT (IP CAMERA / RECORDER) | 128 | 256 | 256 | UNLIMITED |
| CLIENT-SERVER MODE | NO | CLIENT M | YES | |
| MULTIPLE DISPLAY LAYOUT | 1 | 4 | 4 | 8 |
| LIVE VIEW CHANNELS | 32 | 64 | 64 | 96 |
| DPTZ | 1x - 11x | 1X - 11X | 1X - 11X | 1x - 11x |
| JOYSTICK CONTROL | Y | 'ES | YES | YES |
| TOTAL RECORD CH | 16 | 0 | UP TO 64CH | UP TO 64CH |
| E-MAP | | YES | | |

EAGLEEYES APP

Access your AVTECH System from the palm of your hand with your Android and iOS devices with our APP EagleEyes.





Live Record

AVTECH SOLUTION

During live view, you can manually click on the live record icon to record what is going on, and the footage will be saved to Media.



Smart Management

My Favorites allows you to add channels from differentdevicesto one folder as a new device. It becomes easier toaccess all channels you want to see in one video view.



EaZy Search

Video search becomes easier via the calendar view, allowing you to quickly find the date and time you want in one graphical interface. When you find the video you need, you can further select the time range to extract and save the footage to a cloud drive or in the iPhone (Media), or send it by Email.



AVTECH+

AVTECH's newest APP for APPLE TV

- Live View & Playback
- iCloud Sync for Device Management
- Al Event Search
- XVR & NVR Support
- Cost Effective and Convenient Setup





THANK YOU!

Product Line 2024

